

LOCTITE[®] 7855™

December 2006

PRODUCT DESCRIPTION

LOCTITE[®] 7855[™] provides the following product characteristics:

Technology	Aqueous Based
Chemical Type	Dibasic Ester & Water
Appearance	Light grey, viscous lotion
Odor	Floral
Cure	Not applicable
Application	Cleaner

LOCTITE[®] 7855TM is a Heavy-duty hand cleaner, specially formulated for the most difficult to remove soils like polyurethane, paints, primers and adhesives. This product is free from silicone and harsh solvents and contains the four skin conditioners, aloe vera, vitamin E, lanolin and jojoba oil. Additionally, this product has a pleasant floral scent and contains fine Pumice, which adds to the cleaning ability. LOCTITE[®] 7855TM can be used without water, which allows hand cleaning directly at the work place. This product has superior cleaning ability making it best for applications such as removing polyurethane, paint, resins, primers, adhesives, silicones, varnish and enamel. The skin conditioning components in this product allow for the most frequent use without affecting the skin.

TYPICAL PROPERTIES

Specific Gravity @ 25 °C	1.07
Flash Point - See MSDS	
pН	4.5 to 5

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

Caution:

This product may affect painted surfaces. Test before cleaning such surfaces.

Directions for use

- Dispense sufficient amount of LOCTITE[®] 7855[™] onto dry hands
- 2. Rub hand cleaner into hands until dirt or soil is dissolved
- 3. Wipe hands dry with a rag or tissue or rinse with water
- 4. If traces of dirt remain, repeat procedure

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. **Storage below** 8 °C or **greater than 28** °C **can adversely affect product properties**. Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

 $(^{\circ}C \ge 1.8) + 32 = ^{\circ}F$ kV/mm $\ge 25.4 =$ V/mil mm / 25.4 = inches μ m / 25.4 = mil N $\ge 0.225 =$ lb N/mm $\ge 5.71 =$ lb/in N/mm² $\ge 145 =$ psi MPa $\ge 145 =$ psi MPa $\ge 145 =$ psi N·m $\ge 8.851 =$ lb·in N·m $\ge 0.738 =$ lb·ft N·mm $\ge 0.738 =$ lb·ft N·mm $\ge 0.142 =$ oz·in mPa·s = cP

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.



Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. [®] denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0